




E-BAL-H1000-A4860N	
Ballast Type	<b>Metal Halide</b>
Lamp	<b>1000W M47</b>
Circuit Type	<b>CWA</b>
Input Frequency	<b>60HZ</b>

Model_No:	E-BAL-H1000-A4860N			Capacitor (Required)			
Input Voltage	480			Capacitance	24uF±3%		
Operating Current	2.2			Minimum Volts	480V		
Open Circuit Current	1.2			Dry	Diameter	2.87"	
Starting Current	5.7				Height	5.3"	
CCF (*ANSI≤1.8)	1.8			Case Max. Temperature			100°C
Short Circuit Current	Secondary	5.7		Ignitor (Not Required)			
	Input	2.3		Ignitor Model			
Recommended Fuse	6			Pulse Height(kV)			
Input Voltage At Lamp Dropout				Pulse Width (≥u S)			
UL 1029 Bench Top Rise	D						
OCV(Min.)	440						
Input Power	1080W						
Power Factor	≥90%						
Regulation	Line Volts	±10%					
	Lamp Watts	±10%					
Insulation System	Class H, 180°C						
Ballast Dimension	A	2.84"					
	B	4.57"					
Ballast Net Weight	19.2 lbs						
Leads	12"-Cross Link Polyolefin			Min.Starting Temp.	-20°F / -30°C		

Ballast Dimension	Wiring Diagram
	
	<p><b>Capacitor</b></p> 

When Ordering, add suffix for options:

D - with distributor replacement kit (include bracket, capacitor and ignitor as necessary)

Specifications are subject to change without notice.

**IPP International Power Product**  
515 S.Yorbita Road  
City of Industry, CA 91744  
Toll Free: 1-888-539-5586