

E-BAL-H400-AMT60N-PS	
Ballast Type	Metal Halide
Lamp	400W M155 / M135
Circuit Type	Pulse Start CWA
Input Frequency	60HZ

Model No: E-BAL-H400-AMT60N-PS		Capacitor (Required)							
Input Voltage	120	208	240	277	Capacitance	26uF±3%			
Operating Current	3.8	2.2	1.9	1.7	Minimum Volts	350V			
Open Circuit Current	2.7	1.6	1.3	1.2	Dry	Diameter	1.77"		
Starting Current (*ANSI:3.2-5.0)	3.9	3.9	3.9	3.9		Height	3.71"		
CCF (*ANSI≤1.8)	1.7	1.7	1.7	1.7	Short Circuit Current				
	Secondary	4.1	4.1	4.1		4.1			
	Input	2.8	1.6	1.4	1.2	Case Max. Temperature		100°C	
Recommended Fuse	10	7	5	5					
Input Voltage At Lamp Dropout									
UL 1029 Bench Top Rise	D	C	D	D	Ignitor (Required)				
OCV(Min.)	254				Ignitor Model	IGN-02			
Input Power	452W				Pulse Height(kV)	3.0-4.0			
Power Factor	≥90%				Pulse Width (≥u S)	1.3 @ 2.7			
Regulation	Line Volts	±10%							
	Lamp Watts	±10%							
Insulation System	Class H, 180°C								
Ballast Dimension	A	2.3"							
	B	3.9"							
Ballast Net Weight	12.8 lbs								
Leads	12"-Cross Link Polyolefin				Min.Starting Temp.	-20°F / -30°C			

Ballast Dimension	Wiring Diagram
Ignitor	Capacitor

When Ordering, add suffix for options:

D - with distributor replacement kit (include bracket, capacitor and ignitor as necessary)

Specifications are subject to change without notice.

- 2009 Energy Code Compliant.